



Standard Scope of Supply

The Atlas Copco **Pick hammers** are hand-held light pneumatic hammers designed for light demolition and construction work. The pneumatic hammers can be used both horizontally and vertically.

... from bridges to underwater work – there's a lot you can do with these machines.

Special attention has been given to the overall product quality, user friendliness, ease of serviceability, and economical operation to ensure best in class cost of ownership.

Available Models

TEX 09 PS	7/8" x 3-1/4"
TEX 09 PS KL	7/8" x 3-1/4"
TEX 10 PS KL	7/8" x 3-1/4"
TEX 12 PS	7/8" x 3-1/4"
TEX 12 PS KL	7/8" x 3-1/4"

Features

- Vibration Reduced Ergonomic Handle
- One-piece solid body
- Sofstart – make the first blow count
- Air cushions
- Silencers

Benefits

- Up to seven times the trigger time of conventional fixed handled machines
- High comfort and performance, without adding unnecessary weight
- Less maintenance and longer life
- Balanced performance
- Smooth breaking
- Controlled noise emission level

Technical data basic unit

TEX Pneumatic Pick Hammers

		TEX 09 PS	TEX 09 PS KL	TEX 10 PS KL
Type of hammer		Pick	Pick	Pick
Weight	lbs	22.3	26.2	23.6
Length	in	19.7	19.5	19.7
Air consumption at 90 psi	CFM	39.1	39.1	36
Impact rate	BPM	1,800	1,800	1,350
Vibration level 3 axes (ISO 28927-10)	m/s ²	16.1	16.1	22.4
Sound power level guaranteed (2000/14/EC)	Lw, dB(A)	103	105	103
Sound pressure level (ISO 11203)	Lp, r=1m	91	93	91
Tool retainer		cap	kick latch	kick latch
Shank size: Hex	in	7/8" x 3-1/4"	7/8" x 3-1/4"	7/8" x 3-1/4"
Part number		8461 0211 02	8461 0211 06	8461 0211 32

TEX Pneumatic Pick Hammers

		TEX 12 PSKL	TEX 12 PS
Type of hammer		Pick	Pick
Weight	lbs	27.1	23.4
Length	in	21.3	21.3
Air consumption at 90 psi	CFM	47	47
Impact rate	BPM	1,600	1,600
Vibration level 3 axes (ISO 28927-10)	m/s ²	15.4	15.4
Sound power level guaranteed (2000/14/EC)	Lw, dB(A)	105	105
Sound pressure level (ISO 11203)	Lp, r=1m	92	93
Tool retainer		kick latch	cap
Shank size: Hex	in	7/8" x 3-1/4"	7/8" x 3-1/4"
Part number		8461 0211 16	8461 0211 27

Accessories - Shanks

Shank - H 7/8" x 3-1/4"

	Working length (in)	Total length (in)	Tip width (in)	Part number
Moil point	15	18.7	-	3083 3242 00
	39.4	43.1	-	3083 3243 00
Narrow chisel	15	18.7	1	3083 3244 00
	39.4	43.1	1	3083 3245 00
Wide chisel	15	18.7	3	3083 3246 00
Asphalt cutter	15	18.7	5	3083 3269 00
Digging chisel	17.7	21.5	3	3083 3247 00
Digging spade	15.7	19.5	4.7	3083 3248 00
Clay spade	17	20.7	5	3083 3249 00
Wedge chisel	15	18.7	1.4	3083 3250 00
Shaft for tamping pad	12.2	16	-	3083 3251 00
Tamping pad, round	-	-	ø7	3083 3252 10
Tamping pad, square	-	-	7	3083 3239 00
Driver pad, round	-	-	ø4	9245 2817 90

Options / Accessories

The **TEX hammer** range is available with accessories providing flexibility.

Chipping hammers

- Hand hose 1/2" x 10'
 - complete with claw coupling and quick coupling (incl. nipple)
- Hose nipple with seal for 1/2" hose
- Claw coupling, Atlas Copco Standard
- Claw coupling, Atlas Copco Standard with strainer

Pick hammers

- Hand hose 1/2" x 10'
 - complete with claw coupling, wing nut
- Claw coupling, Atlas Copco Standard
- Claw coupling, Atlas Copco Standard with strainer

Supplied Documentation

The unit is delivered with documentation regarding:

- Operating and instruction manual
- Spare parts manual
- Electronic copies of both ASL and AIB.
- Declaration of conformity

Warranty Coverage

12 months from the date of commissioning or 18 months from the date of invoicing from manufacturing company or an Atlas Copco Distribution Center or 1000 hours of operation (whichever occurs first).

Kindly refer the warranty documents provided by manufacturing company for detailed / component wise warranty applicability.

