



Standard Scope of Supply

The Atlas Copco **Chipping hammers** are hand-held light pneumatic hammers designed for light demolition and construction work. The pneumatic hammers can be used both horizontally and vertically.

... from bridges to underwater work – there's a lot you can do with these machines.

Special attention has been given to the overall product quality, user friendliness, ease of serviceability, and economical operation to ensure best in class cost of ownership.

Available Models

TEX 03 PS	3/4" x 2"
TEX 05 P	3/4" x 2"
TEX 05 PE	3/4" x 2"

Features

- Vibration Reduced Ergonomic Handle
- One-piece solid body
- Sofstart – make the first blow count
- Air cushions
- Silencers

Benefits

- Up to seven times the trigger time of conventional fixed handled machines
- High comfort and performance, without adding unnecessary weight
- Less maintenance and longer life
- Balanced performance
- Smooth breaking
- Controlled noise emission level

Technical data basic unit

TEX Pneumatic Chipping Hammers

		TEX 03 PS	TEX 05 P	TEX 05 PE	TEX 05 PH
Type of hammer		Chip	Chip	Chip	Chip
Weight	lbs	8.8	12.1	13.9	12.1
Length	in	11.8	15	17.7	15
Air consumption at 90 psi	CFM	15	20	21.2	20
Impact rate	BPM	4,140	2,760	2,640	2,640
Vibration level 3 axes (ISO 28927-10)	m/s ²	16.5	13	2.4	2.4
Sound power level guaranteed (2000/14/EC)	Lw, dB(A)	105	104	105	105
Sound pressure level (ISO 11203)	Lp, r=1m	89	92	87	87
Tool retainer		cap	cap	cap	cap
Shank size:	in	3/4" x 2"	3/4" x 2"	3/4" x 2"	3/4" x 2"
Part number		8461 0208 01	8461 0219 00	8461 0219 10	8461 0219 01
Part number: kit		8461 0208 02			

Accessories - Shanks

Shank - H 3/4" x 2"

	Working length (in)	Total length (in)	Tip width (in)	Part number
Moil point	9.5	11.8	-	3083 3220 00
	17.3	19.7	-	3083 3221 00
Narrow chisel	9.5	11.8	0.9	3083 3222 00
	17.3	19.7	0.9	3083 3223 00
Wide chisel	7.5	9.8	2.4	3083 3224 00
Shaft for bush hammer	3.2	5.5	-	3083 3225 00
Bush hammer, TC head	Z=0.35	-	1.6	3083 3226 00
	Z=0.63	-	1.6	3083 3227 00
Bush hammer, steel head	-	-	1.25	3083 4163 00

Options / Accessories

The **TEX hammer** range is available with accessories providing flexibility.

Chipping hammers

- Hand hose 1/2" x 10'
 - complete with claw coupling and quick coupling (incl. nipple)
- Hose nipple with seal for 1/2" hose
- Claw coupling, Atlas Copco Standard
- Claw coupling, Atlas Copco Standard with strainer

Pick hammers

- Hand hose 1/2" x 10'
 - complete with claw coupling, wing nut
- Claw coupling, Atlas Copco Standard
- Claw coupling, Atlas Copco Standard with strainer

Supplied Documentation

The unit is delivered with documentation regarding:

- Operating and instruction manual
- Spare parts manual
- Electronic copies of both ASL and AIB.
- Declaration of conformity

Warranty Coverage

12 months from the date of commissioning or 18 months from the date of invoicing from manufacturing company or an Atlas Copco Distribution Center or 1000 hours of operation (whichever occurs first).

Kindly refer the warranty documents provided by manufacturing company for detailed / component wise warranty applicability.

