

Medium pneumatic breakers

Applications:

- Medium breakers for service jobs and general demolition
- TEX P60: asphalt and other medium hard materials

Features:

- Solid Body concept
- Noise-reduction
- HAPS™ Hand and Arm Protection System (PE series)
- SOFSTART™ two-step trigger
- Rotating air inlet swivel
- Integrated lubricator
- Air cushioned piston



Pneumatic breakers		TEX 230PE			TEX 280PE		TEX 33PE		TEX P60S	
Vibro-reduced		YES	YES	YES	YES	YES	YES	YES	NO	NO
Weight	kg	25,5	27	27	31,5	31,5	37	37	33	33
Length	mm	625	670	670	690	690	745	745	690	690
Air consumption	l/s	30	30	30	32	32	34	34	36	36
Impact rate	bpm	1320	1320	1320	1230	1230	1200	1200	1500	1500
Vibration level 3 axes (ISO 28927-10)	m/s ²	4,2	4,2	4,2	4,8	4,8	5,7	5,7	16,8	16,8
Sound power level guaranteed (2000/14/EC)	Lw, dB(A)	104	106	106	105	105	111	111	109	109
Sound pressure level (ISO 11203)	Lp, r=1m	92	93	93	92	92	99	99	97	97
Shank size	Hex mm	25x108	28x160	32x160	28x160	32x160	28x160	32x160	28x160	32x160

Available shank sizes ¹⁾		25x108	28x160	32x160
TEX 230PE	Part number	8461 0225 31	8461 0225 34	8461 0225 35
TEX 280PE	Part number	–	8461 0226 32	8461 0226 33
TEX 33PE	Part number	–	8461 0227 01	8461 0227 00
TEX P60S	Part number	–	8461 0227 22	8461 0227 23

Data at 6 bar (90 psi) air pressure

¹⁾ Hex shank (mm)

TEX P60 S Kit available(Except US & Canada):
8381020056, 8381 0200 55
See page 27 for more information

Suitable couplings:

Atlas Copco Standard	9000 0306 00
Atlas Copco Standard with strainer	9000 0306 01
US Standard	9001 0005 06

Claw couplings not included in delivery