

Heavy pneumatic breakers

Applications:

- Heavy-duty demolition breakers for use in medium and hard materials such as asphalt and reinforced concrete

Features:

- Noise-reduction
- HAPS™ Hand and Arm Protection System (PE series)
- Rotating air inlet swivel
- Integrated lubricator
- Air cushioned piston



Pneumatic breakers		TEX 37*	TEX 40PE		TEX P90S	
Vibro-reduced		NO	YES	YES	NO	NO
Weight	kg	37	42	42	43	43
Length	mm	729	750	750	710	710
Air consumption	l/s	35	40	40	40	40
Impact rate	bpm	1200	1110	1110	1260	1260
Vibration level 3 axes (ISO 28927-10)	m/s ²	19,5	4,2	4,2	15,3	15,3
Sound power level guaranteed (2000/14/EC)	Lw, dB(A)	Not applicable	111	111	111	111
Sound pressure level (ISO 11203)	Lp, r=1m	Not applicable	99	99	99	99
Shank size	Hex mm	32x160	28x160	32x160	28x160	32x160

Available shank sizes ¹⁾		22x82,5	25x108	28x160	32x160
TEX 37	Part number	–	–	–	8461 0229 12
TEX 40PE	Part number	–	–	8461 0228 05	8461 0228 04
TEX P90S	Part number	–	–	8461 0228 22	8461 0228 23

Data at 6 bar (90 psi) air pressure

Claw couplings not included in delivery

¹⁾ Hex shank (mm)

Suitable couplings:

*Available only for India, Middle East & South East Asian countries

Atlas Copco Standard

9000 0306 00

Atlas Copco Standard with strainer

9000 0306 01

US Standard

9001 0005 06

TEX P90S Kit available (except US & Canada): 8381020058

See page 31 for more information