

# KEEP YOUR TOOLS RUNNING

Fuel for outdoor use and electric for indoor use.  
There is a power pack for every occasion and every need.

Our power packs are specialised to power applications in the range that require 20-40 lpm/170 bar. They're light and compact with well protecting frames. Two people can lift and carry the power packs with ease. And they're so small you can stack them on a shelf or in a minivan. The high power to weight ratio means you save both manpower and fuel

during transport. Foldable handles and big wheels also makes it easy to move the power pack around the work site.

Many of the power packs are equipped with Power On Demand (POD). This hydraulic regulatory system automatically idles the engine when the tool is not in use,

and speeds it up when the tool is re-activated.

The thermostatically-controlled oil cooler allows quick warm-ups and helps protect the hydraulic oil from overheating. Correct working temperatures are achieved within minutes – even during the winter.

Power packs - LP		FOR OUTDOOR USE		9-20 P <sup>1</sup>	13-30 P <sup>1,2</sup>	18-30 PE	18-40 PE	18 Twin PE <sup>2</sup>	13-20 DEL <sup>2</sup>
Engine brand		Honda			B&S Vanguard			Lombardini	
Fuel		Petrol			Petrol			Diesel	
Power	hp	9	13	18	18	18	18	10	
Weight (incl oil)	kg	80	91	119	119	123	116	116	
Dimensions (L x W x H)	mm	630x530x640	745x600x705	790x605x745	790x605x745	755x700x720	745x600x705	745x600x705	
Oil flow	l/min	20	20-30	20-30	20-40	2x20/1x40	20	20	
Max pressure	bar	150	150	172	145	145	150	150	
Fuel capacity	l	6	6.5	8.5	8.5	8.5	5	5	
Hose included		yes	yes	no	no	no	no	no	
Power on Demand (POD)		yes	yes	no	no	yes	no	no	
Oil control: engine oil		yes	yes	yes	yes	yes	no	no	
Electric start		no	no	yes	yes	yes	yes	yes	
Sound power level guaranteed (2000/14/EC) <sup>3</sup>	Lw dB(A)	101	101	101	101	101	-	-	
Sound pressure level (ISO 11203) <sup>3</sup>	Lp, r=1m dB(A)	87	89	88	89	89	-	-	
EHTMA class		C	C/D	C/D	C/D/E	C/E	C	C	
Part number		1807 0080 50	1807 0110 12	1807 0160 41	1807 0160 38	1807 0160 16	-	-	

**Non-CE noise approved versions for sale in all markets outside CE**

Part number		1807 0080 51	1807 0110 23	-	1807 0160 40	1807 0160 32	1807 0110 20
-------------	--	--------------	--------------	---	--------------	--------------	--------------

Power packs - LP		FOR INDOOR USE		9-20 E	18-30 E	18-40 E	18 Twin E
Fuel		Electric					
Power	kW	5.5 (3x400 V/16A)	11 (3x400 V/32A)	11 (3x400 V/32A)	11 (3x400 V/32A)	11 (3x400 V/32A)	11 (3x400 V/32A)
Weight (incl oil)	kg	73	131	131	131	135	135
Dimensions (L x W x H)	mm	630x530x640	815x605x745	815x605x745	815x605x745	745x605x705	745x605x705
Oil flow	l/min	20	30	40	40	2x20/1x40	2x20/1x40
Max pressure	bar	150	172	155	155	155	155
Electric start		yes	yes	yes	yes	yes	yes
Sound power level guaranteed (2000/14/EC) <sup>3</sup>	Lw dB(A)	96	101	101	101	101	101
Sound pressure level (ISO 11203) <sup>3</sup>	Lp, r=1m dB(A)	82	87	87	87	86	86
EHTMA class		C	D	E	E	C/E	C/E
Part number		1807 0080 52	1807 0160 43	1807 0160 42	1807 0160 22	1807 0160 22	1807 0160 22

1) A 7 metre extension twin-hose comes as standard with LP9-20 P and LP13-30 P 2) LP13-30 P, LP13-20 DEL, LP18 Twin PE and + LP18 Twin E with tubular stainless steel frame, please see LP13-20 DEL photo above. 3) Important: Full details of measurement is available in the Safety and Operating Instruction of the product. It can be found on [www.acprintshop.com](http://www.acprintshop.com)